NEORMATION PEPORT INFORMATION RESTRI

CENTRAL INTELLIGENCE AGENCY

25X1

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

COUNTRY	Rumania	REPORT		
SUBJECT	Fuel Depot in Tingan	DATE DISTR.	27 Sept. 1955	
		NO. OF PAGES	2	
DATE OF INFO.		REQUIREMENT NO	. RD ·	.25X ²
PLACE ACQUIRED		REFERENCES		
DATE ACQUIRED		This is UNEVALUATED	Information	
	SOURCE EVALUATIONS ARE DEFINITIVE	E. APPRAISAL OF CONTENT IS	TENTATIVE.	25X1

- 1. The fuel depot in Tingan is under the direct jurisdiction of the General Headquarters of the Rumanian Air Force. The depot is located in the Cernica (4425N-2617E) woods about five kilometers east of the Bucharest railroad line, and about one kilometer north of Tingan.
- 2. There is a 2,200 meter cableway from the Cernica railroad station to the depot. The depot is in a 400 by 600 meter area enclosed by two 2.80 meter barbed wire fences on wooden posts; the trees have been removed from the space between the two barbed wire fences and around the area directly in front of the enclosure. There are eight wooden watch towers, 4 to 52 meters high, between the two fences. The towers are equipped with middle searchlights which operate day and night.
- 3. The guard detail for the fuel dUNCODED supplied by troops of Rumanian Air Force technical units stationed in the Bucharest area, and consists of 40 men with an officer in charge. The guard is changed daily; eight fixed posts and three mobile units are on duty. At night, the guard at the main gate is in a tower; during the day, the guard is at the gate.
- In the entire area, there are 32 underground tanks, each 3.50 meters in diameter, and 7 to 8 meters high. The tops of the tanks are covered with mounds of sand and gravel. An iron pipe runs from the tanks and is connected by a rubber hose to conduits above ground level. The pipes are of cast iron and pass in front of each row of tanks.
- 5. The network of fuel conduits leads to a pumping station which is located in the vicinity of the loading ramp. Near the loading ramp are four automatic pumps which unload railroad tank cars. The fuel is removed by trucks.

SIECRET

25X1

STATE X ARMY X NAVY X	AIR	T	181	AEC				
		(Note:	Washing	gton distribution	indicated by "	'X'', Field	distribution b	y "#".)

	[S- R-C- R- B- T		25 X 1
		- 2 -		
				25 X 1
6.	In the depot area, there are building, used as a guard he which houses about 30 perman under the command of a capt.	TO A CO WOOD.	er one-story brick one-story building the depot, who are	
7•		ns about 40 percent jet fue ent ordinary gasoline for m The fuel depot more clo	al, about ho percent	
		Transfer of abote		25X1
	•			
	i			
	; ; •			14

S-E-C-R-E-1